

NEW
in the offer



ISO Certificate:
ISO 9001
ISO 14001



Welding helmet



PYXAR



Welding helmet MOST PYXAR is a combination of unique design of the helmet shell and modern, digitally controlled auto-darkening filter provided with LCD display.

This welding helmet is equipped with head protection, which protects against spatters and disadvantageous out light, thus increasing the user's work comfort and security.

Additionally, MOST PYXAR has specially extruded, thick, scratch-resistant front cover lens. Specially designed shape of the welding helmet protects the external lens from scratching, while the helmet is not in use.

Headgear is highly adjustable according to individuals needs.

The helmet is suitable for any welding process and after pressing the GRIND button, located above the automatic filter, it is also suitable for grinding.

| | |
|---------------------------------------------------|----------------------------------------------------------|
| Optical classes according EN 379:2003 +A1:2009 | 1/1/1 |
| Viewing area | 98 x 62 mm |
| Number of arc detection sensors | 4 |
| Darkening degree - bright | 3 |
| Darkening range | 5-9 / 10-14 |
| Darkening control | Digital on display |
| Delay adjustment | Yes / digital / from 1 to 9 |
| Sensitivity adjustment | Yes / digital / from 1 to 9 |
| Filter switching on/off | Automatic |
| „GRIND“ mode | Yes/ external button |
| Lens darkening reaction time | 0,0001 sec. (in temp. 55°C) |
| Delay from dark to light position | 0,1-0,9 sec. |
| Low current range for TIG | ≥ 2 Amp (DC); ≥ 2 Amp (AC) |
| Low power indicator | Tak / cyfrowy |
| Power source | Solar cells and 2 x CR2032 batteries (replaceable) |
| Head protection | Yes |
| Warranty | 2 years |



unique construction/design - protects external lens from scratching, while the helmet is not in use



specially extruded, thick, scratch-resistant external PC cover lens



highest optical classes according EN 379: 1/1/1/1
4 detection sensors
digitally controlled auto-darkening filter
darkening degree - bright 3
2 darkening range: 5-9 i 10-14 DIN



head protection - protects against spatters and disadvantageous out light



comfortable headgear with longitudinal adjustment - adjustable according to individuals needs



GRIND mode - external button located above the automatic filter